

PRODUCT RECOMMENDATION

# KOMATSU FORKLIFT TRUCKS, LPG/PETROL - BX50 SERIES -16 FG28HTLS- 16 NISSAN K25 TIER 2 (210001A ->)



**ENGINE** Nissan K25  
Capacity: 3,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

*Check every 8 hours, change every 3 months/ 500 hours*

## DIFFERENTIAL

Capacity: 6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 1 months/ 200 hours, change every 6 months/ 1200 hours*

## TORQFLOW TRANSMISSION Torqflow

Capacity: 9,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D**

*Check every 1 months/ 200 hours, change every 6 months/ 1200 hours*

## HYDRAULIC SYSTEM

Capacity: 55 liter (Hydraulic tank)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 32**

PRODUCT RECOMMENDATION 2

**Perlus AF 32**

*Check every 8 hours, change every 6 months/ 1200 hours*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,15 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3**

*Check every 8 hours, change every 6 months/ 1200 hours*

# KOMATSU FORKLIFT TRUCKS, LPG/PETROL - BX50 SERIES -16 FG28HTLS- 16 NISSAN K25 TIER 2 (210001A ->)



## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## COOLING SYSTEM

Capacity: 9,1 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     |          |

*Check every 8 hours, change every 12 months/ 2400 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*