Change every 1 months/ 200 hours

KOMATSU FORKLIFT TRUCKS, **LPG/PETROL - TUSK CX20 SERIES -8** 800CG-8 NISSAN TB45E TIER 1 (130001A ->



ENSINE Missan 18468 Capacity: 8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30		
Check every 8 hours, change every	1 months/ 200 hours		
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30		

DIFFERENTIAL Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 3 months/ 600 hours, of	change every 6 months/ 1200 hours	·

use Normal		climate Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	

Check every 3 months/ 600 hours, change every 6 months/ 1200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1 months/ 200 hours

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	
Change every 1 months/ 200 hours	}	'

KOMATSU FORKLIFT TRUCKS, LPG/PETROL - TUSK CX20 SERIES -8 800CG-8 NISSAN TB45E TIER 1 (130001A ->



TRAME: NEDECAL POWERSHIFT To option Capacity: 16,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 200 hours, change every 6 m	onths/ 1200 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Change every 1 months/ 200 hours		

HYDRAULIC SYSTEM Capacity: 41,64 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	
Check every 8 hours, change every	y 6 months/ 1200 hours	-

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Change every 1 months/ 200 hours

HYDRAULIC BRAKE SYSTEM Capacity: 0,15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
011	11 / 1000 1	

Check every 8 hours, change every 6 months/ 1200 hours

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

PRODUCT RECOMMENDATION

KOMATSU FORKLIFT TRUCKS, **LPG/PETROL - TUSK CX20 SERIES -8** 800CG-8 NISSAN TB45E TIER 1 (130001A ->



COULTE SUSTEM Capacity: 14 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Chook overy 9 hours shange overy	12 months/2400 hours		

Check every 8 hours, change every 12 months/ 2400 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.