

KOMATSU FORKLIFT TRUCKS, LPG/PETROL - TUSK CX50 SERIES -10 900PG-10 NISSAN EBT-TB45E-3A



ENGINE Nissan EBT-TB45E-3A
Capacity: 8,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30

Check every 8 hours, change every 1 months/ 200 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30

Change every 1 months/ 200 hours

DIFFERENTIAL FRONT
Capacity: 10 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 5015	SP Gear 1071

Check every 3 months/ 600 hours, change every 6 months/ 1200 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 5015	SP Gear 1071

Change every 1 months/ 200 hours

TRANSMISSION POWERSHIFT Torqflow
Capacity: 12 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

Check every 1 months/ 200 hours, change every 6 months/ 1200 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

Change every 1 months/ 200 hours

PRODUCT RECOMMENDATION

KOMATSU FORKLIFT TRUCKS, LPG/PETROL - TUSK CX50 SERIES -10 900PG-10 NISSAN EBT-TB45E-3A



HYDRAULIC SYSTEM

Capacity: 74 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Check every 8 hours, change every 6 months/ 1200 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Change every 1 months/ 200 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

Check every 8 hours, change every 6 months/ 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.