

KOMATSU ARTICULATED DUMP TRUCKS

HA/HM HA250-3 KOMATSU S6D125

**ENGINE** Komatsu S6D125

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
<i>Change every 250 hours/ 6 months</i>		

DIFFERENTIAL FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Change every 1000 hours</i>		

DIFFERENTIAL REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Change every 1000 hours</i>		

REDUCTION UNITS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Change every 1000 hours</i>		

KOMATSU ARTICULATED DUMP TRUCKS

HA/HM HA250-3 KOMATSU S6D125



TRANSMISSION POWERSHIFT ZF 6WG200

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SCD 20W-20

Change every 1500 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3
Agrifluid HT

Change every 1500 hours

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SCD 20W-20

Change every 1000 hours

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1
Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3
Agrifluid HT

Change every 1000 hours

HYDRAULIC SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 10W

PRODUCT RECOMMENDATION 2
ATF Dexron II-D

Change every 2000 hours

TANDEM HOUSINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.