## KOMATSU MOTOR GRADERS, SCRAPERS GD/WS GD705A-4 GD705A-21001 ->



ENGINE Komatsu S6D125 Capacity: 30 liter (Dry fill), Capacity: 24 liter (Service fill)				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Multifleet SCD 30				
USE		CLIMATE		
Normal		Cold		
PRODUCT RECOMMENDATION 1				
Multifleet SCD 10W				

CIRCLE REVERSE CASE GEAR Conception of the Capacity: 12 liter	ASE	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 2000 hours		

FINAL DRIVES REAR Capacity: 63 liter (Dry fill), Capacity: 57 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90			
Change every 1000 hours				

TRANSMISSION Capacity: 48 liter (Dry fill), Capacity: 24 liter (Service fill)				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Multifleet SCD 30				
Change every 1000 hours				

## KOMATSU MOTOR GRADERS, SCRAPERS GD/WS GD705A-4 GD705A-21001 ->



Capacity: 140 liter (Dry fill), Capacity: 70 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Multifleet SCD 10W				
Change every 1000 hours				
COOLING SYSTEM Capacity: 55 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant -38 Organic NF	Coolant -26			
TANDEM HOUSINGS Capacity: 105 liter (each)				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Multifleet SCD 30				
Change every 2000 hours				
USE		CLIMATE		
Normal		Cold		
PRODUCT RECOMMENDATION 1				
Multifloot SCD 10W				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Change every 2000 hours