

# KOMATSU WHEELED LOADERS W/WA

## WA150-5 KOMATSU SAA4D102E-2 (2004-2008)



**ENGINE** Komatsu SAA4D102E-2  
Capacity: 12,5 liter (Change capacity), Capacity: 14 liter (Dry fill)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Dieselfleet CD+ 15W-40**

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W****DIFFERENTIAL FRONT**

Capacity: 14 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus****DIFFERENTIAL FRONT LIMITED SLIP**

Capacity: 14 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**DIFFERENTIAL REAR**

Capacity: 14,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus****DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 14,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

# KOMATSU WHEELED LOADERS W/WA

## WA150-5 KOMATSU SAA4D102E-2 (2004-2008)



### HUB REDUCTIONS FRONT

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Agrifluid HT-Plus</b> |  |          |

### HUB REDUCTIONS REAR

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Agrifluid HT-Plus</b> |  |          |

### TRANSFERBOX

Capacity: 4,9 liter

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Multifleet SCD 10W</b> |  |          |

### HYDRAULIC SYSTEM

Capacity: 104 liter (Total)

| USE                       |                          | CLIMATE                  |
|---------------------------|--------------------------|--------------------------|
| Normal                    |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>       | <b>Perlus H 68</b>       |

### CENTRAL LUBRICATION SYSTEM

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

### GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

# KOMATSU WHEELED LOADERS W/WA

## WA150-5 KOMATSU SAA4D102E-2 (2004-2008)

**COOLING SYSTEM**

Capacity: 17 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| Coolant -38 Organic NF   | Coolant -26              |          |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*