

KOMATSU WHEELED LOADERS W/WA

WA200PT-5 KOMATSU SAA6D102E-2 (2004-2008)



ENGINE Komatsu SAA6D102E-2
Capacity: 20 liter

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40

Change every 500 hours

USE	CLIMATE
Normal (preferred)	Moderate

PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		

Change every 12 months

USE	CLIMATE
Acceptable	Mediterranean

PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Change every 250 hours/ 6 months

USE	CLIMATE
Acceptable	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Change every 250 hours/ 6 months

DIFFERENTIAL FRONT
Capacity: 18 liter

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		

USE	CLIMATE
Normal (preferred)	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		

KOMATSU WHEELED LOADERS W/WA

WA200PT-5 KOMATSU SAA6D102E-2 (2004-2008)

**DIFFERENTIAL REAR**

Capacity: 18 liter

USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		

USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		

TRANSFERBOX

Capacity: 7 liter

USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

HYDRAULIC SYSTEM

Capacity: 120 liter

USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Agrifluid HT	

KOMATSU WHEELED LOADERS W/WA

WA200PT-5 KOMATSU SAA6D102E-2 (2004-2008)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Q11 Xtreme Duty Grease EP 2		

COOLING SYSTEM

Capacity: 20 liter

USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 24 months/ 4000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.