KOMATSU WHEELED LOADERS W/WA WA250PZ-6 KOMATSU SAA6D107E-1 (2007-



2017)

ENGINE Komatsu SAA6D107E-1 Capacity: 25,5 liter (Dry fill), Capacity: 23 li	ter (Service fill)	
USE	CI	LIMATE
Normal	N	/loderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		
DIFFERENTIAL FRONT Capacity: 18 liter		

DIFFERENTIAL FRONT Capacity: 18 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	
USE	CLIMATE
Alternative (acceptable)	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	
USE	CLIMATE
Alternative (acceptable)	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

er (Service fill)		
	CLIMATE	
	Moderate	
Ţ	ter (Service fill)	

KOMATSU WHEELED LOADERS W/WA WA250PZ-6 KOMATSU SAA6D107E-1 (2007-



2017)

HYDRAULIC SYSTEM Capacity: 67 liter (Hydraulic tank), Capacity: 135 liter (Total)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	Perlus H 46	
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
	l l	I

CENTRAL LUBRICATION SYSTE	М	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 22 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.