KOMATSU WHEELED LOADERS W/WA WA320-3 KOMATSU S6D114E-1 (1998-2004)



| ENGINE Komatsu S6D114 Capacity: 22,4 liter | | |
|--|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |
| Change every 250 hours/ 6 months | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 | |
| Change every 250 hours/ 6 months | | |

| DIFFERENTIAL FRONT Capacity: 25 liter | | |
|--|---------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agrifluid Synth XHP Ultra | Agrifluid HT-Plus |
| Change every 2000 hours | , | , |

| DIFFERENTIAL REAR Capacity: 25 liter | | |
|---|---------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agrifluid Synth XHP Ultra | Agrifluid HT-Plus |
| Change every 2000 hours | - | 1 |

| TRANSMISSION Capacity: 60 liter | |
|---------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Multifleet SCD 10W | |
| Change every 1000 hours | |

KOMATSU WHEELED LOADERS W/WA WA320-3 KOMATSU S6D114E-1 (1998-2004)



| HYDRAULIC SYSTEM Capacity: 165 liter | |
|--------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Perlus H 46 | |
| Change every 2000 hours | |

| HYDRAULIC BRAKE SYSTEM | | |
|--------------------------|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 46 | | |
| Change every 2000 hours | · | |

| CENTRAL LUBRICATION SYSTE | М | |
|---------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Grease EP 0 | | |

| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |
| USE | | CLIMATE |
| GREASE POINTS/NIPPLES | | |

AIRCONDITIONING

We are unable to give a standard recommendation for this component. Please contact our service department.

PRODUCT RECOMMENDATION

KOMATSU WHEELED LOADERS W/WA WA320-3 KOMATSU S6D114E-1 (1998-2004)



| STEERING SYSTEM | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Perlus H 46 | |
| Change every 2000 hours | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.