

# KOMATSU WHEELED LOADERS W/WA

## WA320-5 JAPAN (2004-2008)



### ENGINE

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Synfleet SHPD 10W-40</b>

*Change every 500 hours*

USE	CLIMATE
Normal (preferred)	Moderate

PRODUCT RECOMMENDATION 1		
<b>Dieselfleet MSP 15W-40</b>		

*Change every 12 months*

USE	CLIMATE
Acceptable	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>

*Change every 250 hours/ 6 months*

### DIFFERENTIAL FRONT

Capacity: 24 liter

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		

USE	CLIMATE
Normal (preferred)	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		

# KOMATSU WHEELED LOADERS W/WA

## WA320-5 JAPAN (2004-2008)



### DIFFERENTIAL REAR

Capacity: 24 liter

USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		

USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		

### TRANSFERBOX

Capacity: 7,2 liter (Refill), Capacity: 8 liter (Total)

USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

### HYDRAULIC SYSTEM

Capacity: 89 liter (Refill), Capacity: 175 liter (Total)

USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>	

# KOMATSU WHEELED LOADERS W/WA WA320-5 JAPAN (2004-2008)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Q11 Xtreme Duty Grease EP 2</b>		

## COOLING SYSTEM

Capacity: 20 liter

USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Change every 24 months/ 4000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*