## KOMATSU WHEELED LOADERS W/WA WA900-3 KOMATSU SA12V140 (2000-2008)



ENGINE Komatsu SA12V140 Capacity: 637 liter, Capacity: 132 liter (Refill), Capacity: 140 liter (Specified)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Change every 250 hours/ 6 months

DIFFERENTIAL FRONT Capacity: 360 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Change every 2000 hours

DIFFERENTIAL REAR Capacity: 360 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Change every 2000 hours

TRANSMISSION Capacity: 140 liter (Refill), Capacity: 164 liter (Specified)		
USE	CLIMATE	
Normal	Mediterranean	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 1000 hours		
USE	CLIMATE	
Normal	Cold	

PRODUCT RECOMMENDATION 1

## Gear Oil Alcat 10W

Change every 1000 hours

## KOMATSU WHEELED LOADERS W/WA WA900-3 KOMATSU SA12V140 (2000-2008)



HYDRAULIC SYSTEM Capacity: 725 liter (Refill), Capacity: 1065 liter (Specified)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 2000 hours

HYDRAULIC BRAKE SYSTEM Capacity: 31 liter (Refill), Capacity: 42 liter	Specified)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

COOLING SYSTEM Capacity: 301 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

PINS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.