

KOMATSU TRACKED EXCAVATORS PC/HB

PC138US-8 (2007-2008)



ENGINE Komatsu SAA4D95LE-3
Capacity: 11,5 liter (Dry fill), Capacity: 11 liter (Service fill)

| USE | CLIMATE |
|----------------------|----------|
| Normal (alternative) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------------|-------------------------------|-----------------------------|
| Agrisynth LSP Ultra FE 5W-30 | Agridiesel CRD+ 15W-40 | Synfleet SHPD 10W-40 |

Change every 500 hours

| USE | CLIMATE |
|--------------------|----------|
| Normal (preferred) | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|-------------------------------|--|--|
| Dieselfleet MSP 15W-40 | | |

Change every 12 months

| USE | CLIMATE |
|------------|---------------|
| Acceptable | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Multifleet SCD 30 | | |

Change every 250 hours/ 6 months

| USE | CLIMATE |
|------------|----------|
| Acceptable | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-----------------------------|-----------------------------|
| Agridiesel CRD+ 15W-40 | Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 |

Change every 250 hours/ 6 months

FINAL DRIVES
Capacity: 2,1 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Gear Oil Alcat 30 | | |

Change every 2000 hours

POWER TAKE OFF
Capacity: 0,75 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Gear Oil Alcat 30 | | |

Change every 1000 hours

KOMATSU TRACKED EXCAVATORS PC/HB

PC138US-8 (2007-2008)



HYDRAULIC SYSTEM

Capacity: 120 liter (Dry fill), Capacity: 69 liter (Service fill)

| USE | | CLIMATE |
|---------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 10W | Perlus H 46 | |

Change every 5000 hours

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

COOLING SYSTEM

Capacity: 12,4 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

SWING REDUCTION UNIT

Capacity: 2,5 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.