KOMATSU TRACKED EXCAVATORS PC/HB PC150LGP-6K



ENGINE Komatsu S4D102E-1 Capacity: 17,5 liter (Dry fill), Capacity: 17 liter (Service fill)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 30			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 10W			

HYDRAULIC SYSTEM Capacity: 140 liter (Dry fill), Capacity: 90 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

COOLING SYSTEM Capacity: 18,2 liter		
USE		CLIMATE
Normal		Moderate
Normal PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	Moderate

SWING GEAR BRAKE UNIT Capacity: 0,75 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

KOMATSU TRACKED EXCAVATORS PC/HB PC150LGP-6K



SWING REDUCTION UNIT Capacity: 2,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

TRAVEL REDUCTION UNIT Capacity: 2,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.