

# KOMATSU TRACKED EXCAVATORS PC/HB

## PC20MR-2 (2005-2010)

**ENGINE** Komatsu 3D76E-5

Capacity: 3,4 liter (Change capacity), Capacity: 3,7 liter (Dry fill)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Check every 10 hours, change every 500 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

## PRODUCT RECOMMENDATION 3

**Dieselfleet CD+ 15W-40***Check every 10 hours, change every 500 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Check every 10 hours, change every 500 hours***HYDRAULIC SYSTEM**

Capacity: 19 liter (Change capacity), Capacity: 29 liter (Complete)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

## PRODUCT RECOMMENDATION 3

**Dieselfleet CD+ 15W-40***Check every 10 hours, change every 2000 hours*

| USE               | CLIMATE  |
|-------------------|----------|
| Biodegradable oil | Moderate |

## PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46***Check every 10 hours, change every 2000 hours***GREASE POINTS/NIPPLES**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Q11 Xtreme Duty Grease EP 2**

# KOMATSU TRACKED EXCAVATORS PC/HB

## PC20MR-2 (2005-2010)



### COOLING SYSTEM

Capacity: 3 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

### TRAVEL REDUCTION UNIT

Capacity: 0,6 liter (each)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Multifleet SCD 30</b> |  |          |

*Change every 1000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*