KOMATSU TRACKED EXCAVATORS PC/HB PC20R-8 KOMATSU 3D78A-3FAE (F30791 ->) (1999-2004)



ENGINE Komatsu 3D78AE-3FA Capacity: 3,6 liter		
USE		CLIMATE
Normal, fuel sulfur level < 0.5 %		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
Change every 250 hours/ 6 months		
USE		CLIMATE
Normal, fuel sulfur level < 0.5 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 20W-20
Change every 250 hours/ 6 months		
USE		CLIMATE
Normal, fuel sulfur level < 0.5 %		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 250 hours/ 6 months		
HYDRAULIC SYSTEM Capacity: 29 liter (Refill), Capacity: 48 liter	(Specified)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 2000 hours	·	

USE	CLIMATE
Biodegradable oil	Moderate
PRODUCT RECOMMENDATION 1	
Perlus Biosynth 46	
Change every 2000 hours	

 GREASE POINTS/NIPPLES

 CLIMATE

 USE
 CLIMATE

 Normal
 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2
 PRODUCT RECOMMENDATION 3

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2
 PRODUCT RECOMMENDATION 3

 Labora Grease
 Q5 MP Calcep Grease EP 2
 MP Lithep Grease EP 2

KOMATSU TRACKED EXCAVATORS PC/HB PC20R-8 KOMATSU 3D78A-3FAE (F30791 ->) (1999-2004)



COOLING SYSTEM Capacity: 4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 2000 hours

TRAVEL REDUCTION UNIT Capacity: 0,7 liter (each hub)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Multifleet SCD 10W				
Check every 250 hours, change every 1000 hours				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				
Multifleet SCD 10W				

Change every 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.