## KOMATSU TRACKED EXCAVATORS PC/HB PC228USLC-3 30001-> (2001-2010)



ENGINE Komatsu SAA6D107E-1 Capacity: 26,3 liter (Dry fill), Capacity: 24 liter (Service fill)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 30			
Change every 250 hours/ 6 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	
Change every 250 hours/ 6 months			
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 10W			
Change every 250 hours/ 6 months	•	'	

FINAL DRIVES Capacity: 5,2-5,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

HYDRAULIC SYSTEM Capacity: 185 liter (Dry fill), Capacity: 126 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	
Change every 2000 hours			

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
GREASE POINTS/NIPPLES		

## KOMATSU TRACKED EXCAVATORS PC/HB PC228USLC-3 30001-> (2001-2010)



COOLING SYSTEM Capacity: 21,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

CARRIER ROLLERS Capacity: 0,08 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

DAMPER CASE Capacity: 0,75 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Change every 2000 hours	·

SWING REDUCTION UNIT Capacity: 6,6 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

TRACK IDLERS Capacity: 0,07 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

## KOMATSU TRACKED EXCAVATORS PC/HB PC228USLC-3 30001-> (2001-2010)



TRACK ROLLERS Capacity: 0,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
	•

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.