

KOMATSU TRACKED EXCAVATORS PC/HB

PC240NLC-3KP



ENGINE

| USE | | CLIMATE |
|---|-------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |
| <i>Change every 250 hours/ 6 months</i> | | |

FINAL DRIVES

| USE | | CLIMATE |
|--------------------------|--|----------|
| Preferred | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |

HYDRAULIC SYSTEM

| USE | | CLIMATE |
|--------------------------------|-----------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |
| <i>Change every 2000 hours</i> | | |

SWING REDUCTION UNIT

| USE | | CLIMATE |
|--------------------------|--|----------|
| Preferred | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.