

KOMATSU TRACKED EXCAVATORS PC/HB

PC290LC-6K K34094 -> (1998-2002)

**ENGINE** Komatsu SA6D102E-1

Capacity: 26,3 liter (Dry fill), Capacity: 23,6 liter (Service fill)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 500 hours*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40*Change every 500 hours*

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 500 hours*

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Armado Synth 5W-30*Change every 500 hours***HYDRAULIC SYSTEM**

Capacity: 248 liter (Dry fill), Capacity: 166 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40*Change every 5000 hours*

| USE | CLIMATE |
|-------------------|----------|
| Biodegradable oil | Moderate |

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46*Change every 5000 hours*

KOMATSU TRACKED EXCAVATORS PC/HB

PC290LC-6K K34094 -> (1998-2002)



GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 100 hours

COOLING SYSTEM

Capacity: 24,4 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Change every 2000 hours/ 12 months

SWING GEAR BRAKE UNIT

Capacity: 0,75 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |

SWING REDUCTION UNIT

Capacity: 5,5 liter

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 50 | | |

Change every 1000 hours

| USE | | CLIMATE |
|------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 20W-20 | | |

Change every 1000 hours

KOMATSU TRACKED EXCAVATORS PC/HB

PC290LC-6K K34094 -> (1998-2002)

**TRAVEL REDUCTION UNIT**

Capacity: 9,5 liter (each)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SCD 50*Change every 2000 hours*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.