

# KOMATSU TRACKED EXCAVATORS PC/HB

## PC300LCSE-8 ECOT3 (2007-2013)



**ENGINE** Komatsu SAA6D114  
Capacity: 38 liter, Capacity: 35 liter (Refill)

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1

**Dieselfleet MSP 15W-40**

*Check every 8 hours, change every 500 hours*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40**

*Check every 8 hours, change every 500 hours*

### HYDRAULIC SYSTEM

Capacity: 365 liter, Capacity: 188 liter (Refill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W**

PRODUCT RECOMMENDATION 2

**Perlus H 46**

*Check every 8 hours, change every 5000 hours*

### GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q11 Xtreme Duty Grease EP 2**

PRODUCT RECOMMENDATION 3

**Q5 MP Calcep Grease EP 2**

*Change every 100 hours*

### COOLING SYSTEM

Capacity: 32 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

*Check every 8 hours, change every 24 months/ 4000 hours*

# KOMATSU TRACKED EXCAVATORS PC/HB

## PC300LCSE-8 ECOT3 (2007-2013)

**DAMPER CASE**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Change every 1000 hours***SWING PINION**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q11 Xtreme Duty Grease EP 2**

PRODUCT RECOMMENDATION 3

**Q5 MP Calcep Grease EP 2***Change every 500 hours***SWING REDUCTION UNIT**

Capacity: 16,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 500 hours, change every 1000 hours***TRAVEL REDUCTION UNIT**

Capacity: 9 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 500 hours, change every 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.