

# KOMATSU TRACKED EXCAVATORS PC/HB

## PC340



### ENGINE

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	
<i>Change every 250 hours/ 6 months</i>		

### FINAL DRIVES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

### HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet CD+ 15W-40</b>
<i>Change every 2000 hours</i>		

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

### DAMPER CASE

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		
<i>Change every 2000 hours</i>		

# KOMATSU TRACKED EXCAVATORS PC/HB PC340



## SWING REDUCTION UNIT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*