## KOMATSU TRACKED EXCAVATORS PC/HB PC450-8 (2007-2013)



<b>ENGINE</b> Komatsu SAA6D125 Capacity: 46 liter, Capacity: 37 liter (Refill)		
USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Check every 8 hours, change every 500 ho	ours	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40

Check every 8 hours, change every 500 hours

HYDRAULIC SYSTEM Capacity: 248 liter (Hydraulic tank), Capacity: 472 liter (System)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 10W	Perlus H 46		
Check every 8 hours, change every 5000 hours			

GREASE POINTS/NIPPLES		
use Normal		CLIMATE
		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

COOLING SYSTEM Capacity: 36 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		
Check every 8 hours, change every	24 months/ 4000 hours		

## KOMATSU TRACKED EXCAVATORS PC/HB PC450-8 (2007-2013)



DAMPER CASE Capacity: 1,07 liter	
use Normal	сымате Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

Check every 1000 hours

SWING REDUCTION UNIT Capacity: 20 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
<u> </u>	 •

Check every 250 hours, change every 1000 hours

TRAVEL REDUCTION UNIT Capacity: 10,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 250 hours, change every 2000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.