## KOMATSU TRACKED EXCAVATORS PC/HB PC750LC-6K K32001-> (1999-2004)



ENGINE Komatsu SAA6D140E-3 Capacity: 61 liter			
use Normal		CLIMATE	
		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	

Change every 250 hours/ 6 months

Capacity: 20 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Multifleet SCD 50	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

POWER TAKE OFF Capacity: 13,5 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

HYDRAULIC SYSTEM Capacity: 800 liter			
use Normal		climate Moderate	
			PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	
Change every 2000 hours	'	·	

## KOMATSU TRACKED EXCAVATORS PC/HB PC750LC-6K K32001-> (1999-2004)



COOLING SYSTEM Capacity: 85 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

CLIMATE
Mediterranean
CLIMATE
Moderate

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.