

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX015-4 KUBOTA D782-E-BH

(S/N <- 63627) (2011-2018)



ENGINE Kubota D782-E
Capacity: 2,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet LSP Ultra 10W-30

Check every 10 hours, change every 500 hours

HYDRAULIC SYSTEM

Capacity: 15,5 liter (Hydraulic tank), Capacity: 28 liter (Total)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 1000 hours

USE		CLIMATE
Breaker use < 40%		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 800 hours

USE		CLIMATE
Breaker use 40 - 60%		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 400 hours

USE		CLIMATE
Breaker use 60 - 80%		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 300 hours

USE		CLIMATE
Breaker use > 80%		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 200 hours

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX015-4 KUBOTA D782-E-BH

(S/N <- 63627) (2011-2018)

**COOLING SYSTEM**

Capacity: 2,7-2,9 liter, Capacity: 0,56 liter (Reserve tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

*Check every 10 hours, change every 24 months***IDLER FRONT**

Capacity: 0,03 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

*Change every 2000 hours***TRACK ROLLER**

Capacity: 0,04 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

*Change every 2000 hours***TRAVEL REDUCTION UNIT**

Capacity: 0,33 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Change every 500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.