

LIEBHERR WHEELED LOADERS L L531B

(1995-1998)

**ENGINE** Liebherr D904T

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

DIFFERENTIAL FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Change every 1000 hours</i>		

DIFFERENTIAL REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Change every 1000 hours</i>		

HUB REDUCTIONS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Change every 1000 hours</i>		

HUB REDUCTIONS REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Change every 1000 hours</i>		

LIEBHERR WHEELED LOADERS L L531B

(1995-1998)



TRANSMISSION Powershift ZF 3 AVG---

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
<i>Change every 1000 hours</i>		

HYDRAULIC SYSTEM

Capacity: 200 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	Multifleet SHPD 15W-40
<i>Change every 2000 hours</i>		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HDX 10W		
<i>Change every 2000 hours</i>		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

HINGES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

LIEBHERR WHEELED LOADERS L L531B

(1995-1998)



SPLITTER GEARBOX

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 8 hours, change every 500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 250 hours/ 6 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.