

# LIEBHERR TRACKED EXCAVATORS R R912 LITRONIC LIEBHERR D924TE (1994- 1998)

**ENGINE** Liebherr D924T-E

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 10 hours, change every 500 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 50 hours*

**HYDRAULIC SYSTEM**

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Multifleet SHPD 10W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>HDX 10W</b>		

*Change every 2000 hours*

**GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

**SWING REDUCTION UNIT WITH POSITIONING PLATE**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

# LIEBHERR TRACKED EXCAVATORS R R912 LITRONIC LIEBHERR D924TE (1994- 1998)



## SWING REDUCTION UNIT WITHOUT POSITIONING PLATE

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

## SWING RING BALL RACE

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## SWING RING GEAR TEETH AUTOMATIC LUBRICATION

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Compound OGL EP 0/1</b>		

## SWING RING GEAR TEETH MANUAL LUBRICATION

We are unable to give a standard recommendation for this component. Please contact our service department.

## TRACK IDLERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

## TRACK ROLLERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

# LIEBHERR TRACKED EXCAVATORS R R912 LITRONIC LIEBHERR D924TE (1994- 1998)



## TRAVEL REDUCTION UNIT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 8 hours, change every 500 hours*

## WIRE ROPES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Compound OGL</b>		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*