

LIEBHERR TRACKED ROPE OPERATED CRANES HS HS853HD D926TI-E (1998 AND AFTER)



ENGINE Liebherr D926TI-E
Capacity: 22 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Check every 8 hours, change every 500 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40

Check every 8 hours, change every 500 hours

TRANSFERBOX
Capacity: 5,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

Check every 8 hours, change every 500 hours

HYDRAULIC SYSTEM
Capacity: 1000 liter (Hydraulic tank)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
SP Matic 2032

PRODUCT RECOMMENDATION 2
ATF Almirol

PRODUCT RECOMMENDATION 3
ATF Dexron II-D

Check every 8 hours, change every 2000 hours

GREASE POINTS/NIPPLES

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
HT Q9 High Grade Grease

PRODUCT RECOMMENDATION 2
Labora Grease

PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2

GREASE POINTS/NIPPLES SWING GEAR

We are unable to give a standard recommendation for this component. Please contact our service department.

LIEBHERR TRACKED ROPE OPERATED CRANES HS HS853HD D926TI-E (1998 AND AFTER)

**COOLING SYSTEM**

Capacity: 70 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 11****PRODUCT RECOMMENDATION 2****Coolant -38 Organic NF****PRODUCT RECOMMENDATION 3****Coolant -26****SWING REDUCTION UNIT**

Capacity: 11 liter (each)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 500 hours, change every 1000 hours***TRAVEL REDUCTION UNIT**

Capacity: 12 liter (each)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 500 hours, change every 1000 hours***WINCH REDUCTION UNIT**

Capacity: 13 liter (12t (each)), Capacity: 16 liter (16t (each)), Capacity: 18 liter (20t (each)), Capacity: 26 liter (25t (each))

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 500 hours, change every 1000 hours***WINCH REDUCTION UNIT MAIN BOOM CONTROL**

Capacity: 3,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 500 hours, change every 1000 hours*

LIEBHERR TRACKED ROPE OPERATED CRANES HS HS853HD D926TI-E (1998 AND AFTER)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.