

# LIFTLUX SELF PROPELLED PLATFORMS, DIESEL SL 260-25DL DEUTZ BF04L 2011F

**ENGINE** Deutz BF04L-2011F

Capacity: 10,5 liter, Filter capacity: 0,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>HDX 20W-50</b>	<b>Multifleet SHPD 20W-50</b>	

*Change every 3 months/ 150 hours*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Change every 3 months/ 150 hours***HYDRAULIC SYSTEM**

Capacity: 350 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 8 hours, change every 1200 hours***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

**HYDRAULIC DRIVE**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 8 hours, change every 1200 hours*

# LIFTLUX SELF PROPELLED PLATFORMS, DIESEL SL 260-25DL DEUTZ BF04L 2011F



## WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*