## LIFTLUX SELF PROPELLED PLATFORMS, DIESEL SL 320-30D DEUTZ F6L914



| Kroontrak MTH 10W-30                                                    | Synfleet SHPD 10W-40     | Dieselfleet CD+ 15W-40   |
|-------------------------------------------------------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1                                                | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal                                                                  |                          | Moderate                 |
| USE                                                                     |                          | CLIMATE                  |
| Change every 3 months/ 150 hours                                        |                          |                          |
| HDX 20W-50                                                              | Multifleet SHPD 20W-50   |                          |
| PRODUCT RECOMMENDATION 1                                                | PRODUCT RECOMMENDATION 2 |                          |
| Normal                                                                  |                          | Mediterranean            |
| USE                                                                     |                          | CLIMATE                  |
| <b>ENGINE</b> Deutz F6L-914<br>Capacity: 15 liter, Filter capacity: 0,5 | liter                    |                          |

Change every 3 months/ 150 hours

| HYDRAULIC SYSTEM<br>Capacity: 450 liter |                          |                          |
|-----------------------------------------|--------------------------|--------------------------|
| USE                                     |                          | CLIMATE                  |
| Normal                                  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra               | Agrifluid HT-Plus        | Kroontrak MTH 10W-30     |

Check every 8 hours, change every 1200 hours

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

| HYDRAULIC DRIVE           |                          |                          |
|---------------------------|--------------------------|--------------------------|
| USE                       |                          | CLIMATE                  |
| Normal                    |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus        | Kroontrak MTH 10W-30     |
|                           |                          |                          |

Check every 8 hours, change every 1200 hours

## LIFTLUX SELF PROPELLED PLATFORMS, DIESEL SL 320-30D DEUTZ F6L914



| WHEEL BEARINGS           |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.