

# LINDE FORKLIFT TRUCKS, DIESEL (359 SERIES) H100 TIER 2 (2006 AND AFTER)



**ENGINE** Cummins QSB5.9  
Capacity: 15 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Check every 10 hours, change every 500 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Armado Synth 5W-30</b>	<b>Dieselfleet LSP Ultra 10W-30</b>	

*Check every 10 hours, change every 500 hours/ 12 months*

**HUB REDUCTIONS**  
Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	

**HYDRAULIC SYSTEM**  
Capacity: 202 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus AF 46</b>	

*Change every 2000 hours*

USE	CLIMATE
Heavy Duty	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus AF 100</b>		

*Change every 2000 hours*

USE	CLIMATE
Normal & Heavy duty	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		

*Change every 2000 hours*

# LINDE FORKLIFT TRUCKS, DIESEL (359 SERIES) H100 TIER 2 (2006 AND AFTER)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

## COOLING SYSTEM

Capacity: 20 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.