## LINDE REACH STACKERS (357-05 SERIES) C4527 CH/5



ENGINE Cummins QSM11		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30	

SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
JSE		CLIMATE
Gearlube GL-5 85W-140		
PRODUCT RECOMMENDATION 1		
DDODUGT DECOMMEND ATION 4		· ·
Normal		Tropical
USE		CLIMATE
DRIVE AXLE GEARS		

HUB REDUCTIONS		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

TRANSMISSION			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		

## LINDE REACH STACKERS (357-05 SERIES) C4527 CH/5



HYDRAULIC SYSTEM Capacity: 800 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus H 46	Perlus AF 46		
Change avery 2000 hours			

Change every 3000 hours

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus H 46	Perlus AF 46		
	-		

CENTRAL LUBRICATION SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gear Grease EP 0		

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
MoS2 Grease EP 2			

COOLING SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

PRODUCT RECOMMENDATION

## LINDE REACH STACKERS (357-05 SERIES) C4527 CH/5



LIFT CHAINS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Industrial Chain Spray			

## TELESCOPIC SPREADER SLEWING GEARUNIT

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.