

LJUNGBY MASKIN WHEELED LOADERS

L13 MERCEDES (2008-2009)



ENGINE Mercedes-Benz OM906LA
Capacity: 24-25 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 |

Check every 10 hours, change every 500 hours

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 |

Check every 10 hours, change every 250 hours

DIFFERENTIAL HUB REDUCTIONS FRONT
Capacity: 30 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| Agrifluid HT-Plus | Agrifluid HT |

Check every 100 hours, change every 1000 hours

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| Agrifluid HT-Plus | Agrifluid HT |

Check every 100 hours, change every 500 hours

DIFFERENTIAL HUB REDUCTIONS REAR
Capacity: 30 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| Agrifluid HT-Plus | Agrifluid HT |

Check every 100 hours, change every 1000 hours

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| Agrifluid HT-Plus | Agrifluid HT |

Check every 100 hours, change every 500 hours

LJUNGBY MASKIN WHEELED LOADERS

L13 MERCEDES (2008-2009)



TRANSMISSION ZF Ergopower WG 190 5/3
Capacity: 21 liter (Service fill), Capacity: 27 liter (Total)

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032 | ATF Almirol | ATF Dexron II-D |

Check every 10 hours, change every 1000 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032 | ATF Almirol | ATF Dexron II-D |

Check every 10 hours, change every 500 hours

HYDRAULIC SYSTEM
Capacity: 115 liter (Service fill), Capacity: 185 liter (Total)

| USE | | CLIMATE |
|---------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 46 | Perlus H 46 | |

Check every 10 hours, change every 2000 hours/ 12 months

| USE | | CLIMATE |
|---------------------------|--------------------------|----------|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 46 | Perlus H 46 | |

Check every 10 hours, change every 6 months/ 1000 hours

CENTRAL LUBRICATION SYSTEM GREASE Lincoln

| USE | | CLIMATE |
|--------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| HT Q9 High Grade Grease | | |

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

LJUNGBY MASKIN WHEELED LOADERS

L13 MERCEDES (2008-2009)



COOLING SYSTEM

Capacity: 30 liter (Service fill), Capacity: 35 liter (Total)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Coolant SP 15+ | Coolant SP 12 | |

Check every 10 hours, change every 12 months/ 4000 hours

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Coolant SP 15+ | Coolant SP 12 | |

Check every 10 hours, change every 6 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.