LULL TELEHANDLERS 1044C-54 JOHN DEERE 6068D



ENGINE John Deere 6068 D Capacity: 13,2 liter		
use Normal		CLIMATE
		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

DIFFERENTIAL FRONT Capacity: 12,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

DIFFERENTIAL REAR Capacity: 12,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

HUB REDUCTIONS FRONT

Capacity: 1,7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS REAR

Capacity: 1,7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

LULL TELEHANDLERS 1044C-54 JOHN DEERE 6068D



TRANSMISSION POWERSHIFT 4/3 Capacity: 16 liter (Complete), Capacity: 10,4 liter (Service fill)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

HYDRAULIC SYSTEM Capacity: 246 liter (Complete), Capacity: 167 liter (Hydra	ulic tank)
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 17 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.