LULL TELEHANDLERS 844C-42 JOHN DEERE 4045T



| ENGINE John Deere 4045 T Capacity: 13,2 liter | | | |
|--|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Mediterranean | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Multifleet SCD 40 | Multifleet SCD 30 | | |
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 | |

| DIFFERENTIAL FRONT Capacity: 12,1 liter | | |
|--|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

| DIFFERENTIAL REAR Capacity: 12,1 liter | | |
|--|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

HUB REDUCTIONS FRONT

Capacity: 1,7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS REAR

Capacity: 1,7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

LULL TELEHANDLERS 844C-42 JOHN DEERE 4045T



| TRANSMISSION POWERSHIFT 4/3 Capacity: 16 liter (Complete), Capacity: 10 | 0,4 liter (Service fill) | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 10W-40 |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Kroontrak MTH 10W-30 | | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Agrifluid HT |

| HYDRAULIC SYSTEM Capacity: 246 liter (Complete), Capacity: 167 liter (Hydraulic tank) | | | |
|---|----------|--|--|
| USE | CLIMATE | | |
| Normal | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | |
| Perlus H 32 | | | |

| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |
|--------------------------|--------------------------|--------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Normal | | Moderate | |
| USE | | CLIMATE | |
| GREASE POINTS/NIPPLES | | | |

| COOLING SYSTEM Capacity: 17 liter | | | |
|-----------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.