

# MANITOU MANISCOPIC MRT MRT 2150 PRIVILEGE E3 MERCEDES-BENZ OM904LA (413080 ->)



**ENGINE** Mercedes-Benz OM904LA  
Capacity: 15 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Check every 10 hours, change every 500 hours/ 12 months*

**DIFFERENTIAL FRONT**  
Capacity: 11 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Agrifluid HT</b>      |  |  |

*Check every 250 hours, change every 1000 hours/ 12 months*

**DIFFERENTIAL REAR**  
Capacity: 11 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Agrifluid HT</b>      |  |  |

*Check every 250 hours, change every 1000 hours/ 12 months*

**HUB REDUCTIONS FRONT**  
Capacity: 1,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Agrifluid HT</b>      |  |  |

*Check every 250 hours, change every 1000 hours/ 12 months*

**HUB REDUCTIONS REAR**  
Capacity: 1,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Agrifluid HT</b>      |  |  |

*Check every 250 hours, change every 1000 hours/ 12 months*

# MANITOU MANISCOPIC MRT MRT 2150 PRIVILEGE E3 MERCEDES-BENZ OM904LA (413080 ->)

**REDUCTION UNIT FRONT 2/2**

Capacity: 2,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agrifluid HT***Check every 250 hours, change every 1000 hours/ 12 months***HYDRAULIC SYSTEM HYDROSTATIC DRIVE**

Capacity: 210 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Perlus H 46***Check every 50 hours, change every 1000 hours/ 12 months***GREASE POINTS/NIPPLES**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2***Change every 50 hours***COOLING SYSTEM**

Capacity: 18 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF***Check every 10 hours, change every 1500 hours***SWING REDUCTION UNIT**

Capacity: 2,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Abacot MEP HD 150**

PRODUCT RECOMMENDATION 2

**Abacot MEP 150***Check every 250 hours, change every 1000 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

**MANITOU MANISCOPIC MRT MRT 2150  
PRIVILEGE E3 MERCEDES-BENZ OM904LA  
(413080 ->)**



*information contained herein is subject to changes without notification.*