

MANITOU MANISCOPIC MT/MTA MT 1135 HA ST3B PERKINS 854E-E34TA STAGE IIIB (2014 AND AFTER)



ENGINE Perkins 854E-E34TA
Capacity: 7,5 liter

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40*Change every 50 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth MSP 10W-40*Change every 50 hours*

USE	CLIMATE
Normal, fuel sulfur level < 0,001 %	Mediterranean

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40*Check every 8 hours, change every 500 hours*

USE	CLIMATE
Normal, fuel sulfur level < 0,001 %	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth MSP 10W-40*Check every 8 hours, change every 500 hours*

DIFFERENTIAL FRONT Dana
Capacity: 7,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 250 hours, change every 500 hours/ 12 months*

DIFFERENTIAL REAR Dana
Capacity: 7,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT*Check every 250 hours, change every 500 hours/ 12 months*

MANITOU MANISCOPIC MT/MTA MT 1135 HA ST3B PERKINS 854E-E34TA STAGE IIIB (2014 AND AFTER)

**HUB REDUCTIONS FRONT**

Capacity: 0,75 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 250 hours, change every 1000 hours/ 24 months***HUB REDUCTIONS REAR**

Capacity: 0,75 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 250 hours, change every 1000 hours/ 24 months***TRANSMISSION POWERSHIFT Dana 4/4**

Capacity: 21,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Almirol*Check every 50 hours, change every 1000 hours/ 24 months***HYDRAULIC SYSTEM**

Capacity: 175 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46*Check every 50 hours, change every 1000 hours/ 24 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

LHM +*Check every 50 hours, change every 2000 hours/ 24 months*

MANITOU MANISCOPIC MT/MTA MT 1135 HA ST3B PERKINS 854E-E34TA STAGE IIIB (2014 AND AFTER)

**COOLING SYSTEM**

Capacity: 17 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.