

# MERLO ACCESS PLATFORMS MPR MPR 20

## (2008 AND AFTER)



**ENGINE** Deutz  
Capacity: 8,5 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Multifleet SHPD 10W-40**

**PRODUCT RECOMMENDATION 2**  
**Multifleet SHPD 15W-40**

**DIFFERENTIAL FRONT**  
Capacity: 5,3 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Gearlube GL-5 80W-90**

**PRODUCT RECOMMENDATION 2**  
**Unigear HS GL-3/GL-5 80W-90**

*Change every 1500 hours*

**DIFFERENTIAL REAR**  
Capacity: 5,3 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Gearlube GL-5 80W-90**

**PRODUCT RECOMMENDATION 2**  
**Unigear HS GL-3/GL-5 80W-90**

*Change every 1500 hours*

**HUB REDUCTIONS FRONT**  
Capacity: 1,3 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Gearlube GL-5 80W-90**

**PRODUCT RECOMMENDATION 2**  
**Unigear HS GL-3/GL-5 80W-90**

*Change every 1500 hours*

**HUB REDUCTIONS REAR**  
Capacity: 1,3 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Gearlube GL-5 80W-90**

**PRODUCT RECOMMENDATION 2**  
**Unigear HS GL-3/GL-5 80W-90**

*Change every 1500 hours*

# MERLO ACCESS PLATFORMS MPR MPR 20

## (2008 AND AFTER)



### TRANSMISSION HYDROSTATIC

Capacity: 12 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

Change every 1500 hours

### HYDRAULIC SYSTEM

Capacity: 120 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

Change every 1500 hours

### HYDRAULIC BRAKE SYSTEM

Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Q7 MP Calcep Grease WR 2</b>	<b>Caliplex HD Grease EP 2</b>	<b>Q5 MP Calcep Grease EP 2</b>

### COOLING SYSTEM

Capacity: 12 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.