

# MERLO TELESCOPIC HANDLERS, PANORAMIC P60.10 XS PERKINS 1004.4



## ENGINE Perkins 1004.4

| USE                         |                               | CLIMATE                     |
|-----------------------------|-------------------------------|-----------------------------|
| Normal                      |                               | Moderate                    |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3    |
| <b>Kroontrak CVT 10W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Kroontrak MTH 10W-30</b> |

*Change every 400 hours/ 6 months*

| USE                         |                               | CLIMATE                     |
|-----------------------------|-------------------------------|-----------------------------|
| Initial service             |                               | Moderate                    |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3    |
| <b>Kroontrak CVT 10W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Kroontrak MTH 10W-30</b> |

*Change every 100 hours*

## DIFFERENTIAL

Capacity: 5,3 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 400 hours/ 6 months*

## GEARBOX

Capacity: 4 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 400 hours/ 6 months*

## HUB REDUCTIONS

Capacity: 1,3 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 400 hours/ 6 months*

# MERLO TELESCOPIC HANDLERS, PANORAMIC P60.10 XS PERKINS 1004.4


**TRANSMISSION HYDROSTATIC** Rexroth

Capacity: 12 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Perlus H 46**

Change every 1600 hours/ 12 months

**HYDRAULIC SYSTEM**

Capacity: 95 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Perlus H 46**

Change every 1600 hours/ 12 months

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0,3 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**
**COOLING SYSTEM**

Capacity: 12 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

## PRODUCT RECOMMENDATION 2

**Coolant -26**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.