

MITSUBISHI FORKLIFT TRUCKS, DIESEL

FD15N EF16D-000111->

**ENGINE**

Capacity: 3,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak MTH 10W-30***Change every 500 hours/ 3 months***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak MTH 10W-30***Change every 1 months***DIFFERENTIAL**

Capacity: 5 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Gearlube GL-4 80W-90****PRODUCT RECOMMENDATION 2****Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 3****Unigear HS GL-3/GL-5 80W-90***Change every 6 months/ 1200 hours***USE**

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Agrifluid HT-Plus****PRODUCT RECOMMENDATION 2****SP Gear 5015****PRODUCT RECOMMENDATION 3****SP Gear 1071***Change every 6 months/ 1200 hours***TRANSFERBOX**

Capacity: 5 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Gearlube GL-4 80W-90****PRODUCT RECOMMENDATION 2****Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 3****Unigear HS GL-3/GL-5 80W-90***Change every 6 months/ 1200 hours***USE**

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Agrifluid HT-Plus****PRODUCT RECOMMENDATION 2****SP Gear 5015****PRODUCT RECOMMENDATION 3****SP Gear 1071***Change every 6 months/ 1200 hours*

MITSUBISHI FORKLIFT TRUCKS, DIESEL

FD15N EF16D-000111->



TRANSMISSION Powershift

Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Change every 6 months/ 1200 hours*

HYDRAULIC SYSTEM

Capacity: 28 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32*Change every 12 months/ 2400 hours*

HYDRAULIC BRAKE SYSTEM

Capacity: 0,14 liter (Reservoir)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Change every 12 months/ 2400 hours*

GREASE POINTS/NIPPLES CHASSIS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Grease EP 1

COOLING SYSTEM

Capacity: 6,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Change every 12 months/ 2400 hours*

MITSUBISHI FORKLIFT TRUCKS, DIESEL FD15N EF16D-000111->

**WHEEL BEARINGS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.