

MITSUBISHI TRANSPORT REFRIGERATION SYSTEMS TNW7E



ENGINE Mitsubishi L3E
Capacity: 9,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	

Change every 250 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
AgriDiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Change every 250 hours/ 12 months

COOLING SYSTEM

Capacity: 1,2 liter (Engine only)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 24 months

REFRIGERATING SYSTEM

Capacity: 3,6 kg

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.