PRODUCT RECOMMENDATION

NEW HOLLAND WHEELED EXCAVATORS MH/WE WE230 CNH 667TA/MEE TIER 3A (2008-2012)

ENGINE CNH 667TA/MEE
Capacity: 16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	**Agridiesel CRD+ 15W-40**	**Dieselfleet CD+ 15W-40**

DIFFERENTIAL FRONT
Capacity: 12,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR
Capacity: 12 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS FRONT
Capacity: 2,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS REAR
Capacity: 2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION POWERSHIFT
Capacity: 2,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC SYSTEM
Capacity: 330 liter (Hydraulic system including tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus H 68		

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

NEW HOLLAND WHEELED EXCAVATORS MH/WE WE230 CNH 667TA/MEE TIER 3A (2008-2012)

SLEWING RING GEARING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM
Capacity: 29 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	**Coolant SP 12**	

SWING REDUCTION UNIT
Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367