

# NEW HOLLAND BACKHOE LOADERS

## B/LB/NH B110C TC FPT F5HFL413B\*A TIER 4I (2012 AND AFTER)



**ENGINE** FPT F5HFL413B  
Capacity: 14 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3     |
|-----------------------------------|-----------------------------|------------------------------|
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

**DIFFERENTIAL FRONT**  
Capacity: 8,6 liter (2WS), Capacity: 10,5 liter (4WS)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1            |  |  |
|-------------------------------------|--|--|
| <b>Unigear LS GL-3/GL-5 85W-140</b> |  |  |

**DIFFERENTIAL REAR**  
Capacity: 15,5 liter (2WS), Capacity: 11 liter (4WS)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1            |  |  |
|-------------------------------------|--|--|
| <b>Unigear LS GL-3/GL-5 85W-140</b> |  |  |

**HUB REDUCTIONS FRONT**  
Capacity: 1 liter (2WS, each), Capacity: 1,3 liter (4WS, each)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1            |  |  |
|-------------------------------------|--|--|
| <b>Unigear LS GL-3/GL-5 85W-140</b> |  |  |

**HUB REDUCTIONS REAR**  
Capacity: 1,3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1            |  |  |
|-------------------------------------|--|--|
| <b>Unigear LS GL-3/GL-5 85W-140</b> |  |  |

# NEW HOLLAND BACKHOE LOADERS

## B/LB/NH B110C TC FPT F5HFL413B\*A TIER 4I (2012 AND AFTER)

**TRANSMISSION POWERSHIFT** Carraro 4/4 4/4

Capacity: 20,8 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Agrifluid HT-Plus</b> |  |          |

**TRANSMISSION POWERSHUTTLE** Carraro 4/3 4/3

Capacity: 18,5 liter (2WD), Capacity: 20,8 liter (4WD)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Agrifluid HT-Plus</b> |  |          |

**HYDRAULIC SYSTEM**

Capacity: 75 liter (Tank), Capacity: 118 liter (Total)

| USE                      |                             | CLIMATE                  |
|--------------------------|-----------------------------|--------------------------|
| Normal                   |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

**GREASE POINTS/NIPPLES**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

**COOLING SYSTEM**

Capacity: 24 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.