## NEW HOLLAND BACKHOE LOADERS B/LB/NH B200 CNH 445T/M2 (2006-2007)



ENGINE CNH 445T/M2 Capacity: 12,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40
Change every 500 hours		

DIFFERENTIAL FRONT Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

<b>DIFFERENTIAL REAR</b> Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

HUB REDUCTIONS FRONT Capacity: 1 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

HUB REDUCTIONS REAR Capacity: 1 liter (each)		
use Normal		CLIMATE
		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

## NEW HOLLAND BACKHOE LOADERS B/LB/NH B200 CNH 445T/M2 (2006-2007)



TRANSMISSION POWERSHIFT Capacity: 18 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

HYDRAULIC SYSTEM Capacity: 80 liter (Tank), Capacity:	118 liter (Total)	
use Normal		CLIMATE
		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

HYDRAULIC BRAKE SYSTEM Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
LHM +	

GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 24 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.