

NEW HOLLAND MINI EXCAVATORS

E/EC/EH E22.2 SR YANMAR 3TNV82A-SYB

(2006-2012)



ENGINE Yanmar 3TNV82
Capacity: 5,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

Change every 500 hours

TENSIONER ROLLERS
Capacity: 0,45 liter (each)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

TRACK ROLLERS + TENSIONERS

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Q7 MP Calcep Grease WR 2

PRODUCT RECOMMENDATION 2
Caliplex HD Grease EP 2

PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2

HYDRAULIC SYSTEM
Capacity: 20 liter (Tank), Capacity: 25 liter (Total)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Perlus Biosynth 46

PRODUCT RECOMMENDATION 2
Perlus H 46

GREASE POINTS/NIPPLES

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Q7 MP Calcep Grease WR 2

PRODUCT RECOMMENDATION 2
Caliplex HD Grease EP 2

PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2

NEW HOLLAND MINI EXCAVATORS

E/EC/EH E22.2 SR YANMAR 3TNV82A-SYB

(2006-2012)

**COOLING SYSTEM**

Capacity: 3,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

SWING GEAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

TRAVEL REDUCTION UNIT

Capacity: 0,35 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

UPPER ROLLERS

Capacity: 0,35 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.