Agridiesel CRD+ 15W-40

NEW HOLLAND WHEELED LOADERS LW/W W130 CNH NF 6 TAA-6802 EU STAGE 2 / TIER 2 (2005-2007)



Multifleet SHPD 15W-40

ENGINE CNH NEF 6 TAA-6802
Capacity: 15 liter

USE

Normal

PRODUCT RECOMMENDATION 1

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40

DIFFERENTIAL FRONT Capacity: 22 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Unigear LS GL-3/GL-5 85W-140	
Change every 1000 hours	·

DIFFERENTIAL REAR Capacity: 24 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Unigear LS GL-3/GL-5 85W-140	
Change every 1000 hours	

TRANSMISSION POWERSHIFT 4/Capacity: 18,5 liter	3	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
Change every 1000 hours	1	

HYDRAULIC SYSTEM Capacity: 63 liter (Tank), Capacity: 113,6 liter (Total)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 46	Perlus H 46		
Change every 2000 hours			

PRODUCT RECOMMENDATION

NEW HOLLAND WHEELED LOADERS LW/W W130 CNH NF 6 TAA-6802 EU STAGE 2 / TIER 2 (2005-2007)



GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

COOLING SYSTEM Capacity: 22 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		
Change every 2000 hours	'	'	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.