NEW HOLLAND WHEELED LOADERS LW/W W170C TC FPT F4HFE613Y TIER 4I (2012-



2016)

Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
ENGINE FPT F4HFE613Y Capacity: 13,2 liter		

AXLE FRONT ZF MT-L3085-II Capacity: 35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

AXLE REAR ZF MT-L3075-II Capacity: 23 liter			
use Normal		climate Moderate	
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT	

TRANSMISSION POWERSHIFT 4/3 Capacity: 34 liter			
use Normal		сымате Moderate	
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT	

TRANSMISSION POWERSHIFT 5/3			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT	

PRODUCT RECOMMENDATION

NEW HOLLAND WHEELED LOADERS LW/W W170C TC FPT F4HFE613Y TIER 4I (2012-



2016)

HYDRAULIC SYSTEM Capacity: 90,8 liter (Tank), Capacity: 177,8 liter (Total)			
use Normal		climate Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 46	Perlus H 46		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 28,4 liter			
use Normal		CLIMATE	
		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.