NEW HOLLAND WHEELED LOADERS LW/W W190C ZB FPT F4HFE613X TIER 4I (2011-



2012)

ENGINE FPT F4HFE613X Capacity: 13,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

DIFFERENTIAL FRONT ZF MT-L3095-II Capacity: 40 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT	

DIFFERENTIAL REAR ZF MT-L3085-II Capacity: 40 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT	

TRANSMISSION POWERSHIFT 4/3 Capacity: 34 liter			
use Normal		сымате Moderate	
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT	

TRANSMISSION POWERSHIFT 5/3		
	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Kroontrak MTH 10W-30	Agrifluid HT	

PRODUCT RECOMMENDATION

NEW HOLLAND WHEELED LOADERS LW/W W190C ZB FPT F4HFE613X TIER 4I (2011-



2012)

HYDRAULIC SYSTEM Capacity: 90,8 liter (Tank), Capacity: 177,8 liter (Total)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 46	Perlus H 46		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 30 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.