

# NEW HOLLAND WHEELED LOADERS LW/W W270C FPT F2CFE614C TIER 4I (2012-2015)



**ENGINE** New Holland/FPT F2CFE614C Tier 4i  
Capacity: 28,5 liter

|        |          |
|--------|----------|
| USE    | CLIMATE  |
| Normal | Moderate |

|                                   |                             |                              |
|-----------------------------------|-----------------------------|------------------------------|
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3     |
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

*Check every 10 hours, change every 500 hours*

## DIFFERENTIAL FRONT

Capacity: 62 liter (Heavy Duty), Capacity: 42 liter (Standard)

|        |          |
|--------|----------|
| USE    | CLIMATE  |
| Normal | Moderate |

|                          |                             |                          |
|--------------------------|-----------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

*Check every 500 hours, change every 1500 hours*

## DIFFERENTIAL REAR

Capacity: 42 liter (all)

|        |          |
|--------|----------|
| USE    | CLIMATE  |
| Normal | Moderate |

|                          |                             |                          |
|--------------------------|-----------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

*Check every 500 hours, change every 1500 hours*

## HUB REDUCTIONS FRONT

|        |          |
|--------|----------|
| USE    | CLIMATE  |
| Normal | Moderate |

|                          |                             |                          |
|--------------------------|-----------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

*Check every 500 hours, change every 1500 hours*

## HUB REDUCTIONS REAR

|        |          |
|--------|----------|
| USE    | CLIMATE  |
| Normal | Moderate |

|                          |                             |                          |
|--------------------------|-----------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

*Check every 500 hours, change every 1500 hours*

# NEW HOLLAND WHEELED LOADERS LW/W W270C FPT F2CFE614C TIER 4I (2012-2015)



## TRANSMISSION POWERSHIFT 4/3

Capacity: 45,4 liter

| USE                         |                             | CLIMATE                       |
|-----------------------------|-----------------------------|-------------------------------|
| Normal                      |                             | Moderate                      |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |

Check every 50 hours, change every 1500 hours

## HYDRAULIC SYSTEM

Capacity: 134 liter (Hydraulic tank), Capacity: 250 liter (System)

| USE                       |                          | CLIMATE  |
|---------------------------|--------------------------|----------|
| Preferred                 |                          | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>       |          |

Check every 50 hours, change every 2000 hours

| USE                       |                          | CLIMATE  |
|---------------------------|--------------------------|----------|
| Alternative (acceptable)  |                          | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>       |          |

Check every 50 hours, change every 2000 hours

## COOLING SYSTEM

Capacity: 56,8 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     |          |

Check every 50 hours, change every 2000 hours

## SCR SYSTEM

Capacity: 91 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*