## NEW HOLLAND TRACKED EXCAVATORS E E265 EL CNH F4AE0684L\*D101 TIER 2 (2005-2007)



2007)

ENGINE CNH F4AE0684L Capacity: 17 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40
Change every 500 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40
Change every 50 hours		·

TRAVEL REDUCTION UNITS Capacity: 3,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 2000 hours	,	

HYDRAULIC SYSTEM Capacity: 180 liter (Tank), Capacity: 280 liter (Total)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Perlus Biosynth 46	Perlus H 46			
Change every 2500 hours				

сlімате Moderate
Moderate
PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION

## NEW HOLLAND TRACKED EXCAVATORS E E265 EL CNH F4AE0684L\*D101 TIER 2 (2005-2007)



COOLING SYSTEM
Capacity: 23 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Coolant SP 15+

Coolant SP 12

Coolant SP 15

Change every 2000 hours

SWING GEAR	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

SWING REDUCTION UNIT Capacity: 15,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1000 hours		•

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.