

NEW HOLLAND TRACKED EXCAVATORS E E335 MITSUBISHI 6D16-TLU2D (2005-2005)



ENGINE Mitsubishi 6D16-TLU2D
Capacity: 28 liter

USE Normal	CLIMATE Tropical
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50	
--	--

Change every 500 hours

USE Normal	CLIMATE Mediterranean
----------------------	---------------------------------

PRODUCT RECOMMENDATION 1 Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40
--	--

Change every 500 hours

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 10W-40
--	--	--

Change every 500 hours

USE Initial service	CLIMATE Tropical
-------------------------------	----------------------------

PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50	
--	--

Change every 50 hours

USE Initial service	CLIMATE Mediterranean
-------------------------------	---------------------------------

PRODUCT RECOMMENDATION 1 Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40
--	--

Change every 50 hours

USE Initial service	CLIMATE Moderate
-------------------------------	----------------------------

PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 10W-40
--	--	--

Change every 50 hours

ROLLERS + IDLERS

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Multifleet SCD 30	
---	--

NEW HOLLAND TRACKED EXCAVATORS E E335 MITSUBISHI 6D16-TLU2D (2005-2005)



TRAVEL REDUCTION UNITS

Capacity: 10,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 2000 hours

HYDRAULIC SYSTEM

Capacity: 351 liter (System), Capacity: 206 liter (Tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Perlus H 46	Perlus H 68

Change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Perlus H 32	

Change every 2000 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	
Perlus H 22	

Change every 2000 hours

COOLING SYSTEM

Capacity: 15 liter (Radiator), Capacity: 34 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Coolant SP 15+	Coolant SP 12

Change every 2000 hours

NEW HOLLAND TRACKED EXCAVATORS E E335 MITSUBISHI 6D16-TLU2D (2005-2005)



SWING REDUCTION UNIT

Capacity: 21,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.