## NEW HOLLAND SKID STEER LOADERS L/LS/LX/SL LS190.B CNH 445M2 (2005-2007)



DN 3
N-40

Change every 100 hours

TRANSFERBOX Capacity: 1,32 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1000 hours		

HYDRAULIC SYSTEM Capacity: 18,9 liter (Tank), Capacity: 56,8 liter (Total)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT	
Change every 1000 hours	'	'	

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
MoS2 Grease EP 2			

COOLING SYSTEM Capacity: 17 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		
	<u> </u>		

## NEW HOLLAND SKID STEER LOADERS L/LS/LX/SL LS190.B CNH 445M2 (2005-2007)



CHAIN CASE Capacity: 11,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.